

## Oil Type/Medium Distribution Transformers

kVA	HV1 (V)	HV2 (V)	LV1 (V)	Vector Group	Impedance (%)	No-Load Loss (W)	Load Loss (W)	Noise level (dB)	Total weight (kg)	Oil weight (kg)	Length (mm)	Width (mm)	Height (mm)	Wheel base (mm)	Tank description
315	26000	0	400	Dyn11	4	980	4130	64	1550	370	1300	900	1700	670	▲
315	20000	8000	400	Dyn11	4	1050	4200	53	1300	0	1240	800	1400	670	▲
315	15000	0	400	Dyn11	4	1050	4200	53	1300	0	1240	800	1400	670	▲
315	10000	0	400	Dyn11	4	1050	4200	53	1300	0	1240	800	1400	670	▲
400	35000	0	400	Dyn1	6	620	5000	50	2050	0	1300	900	1800	670	▲
400	21000	0	420	Dyn5	4	750	4600	63	1560	340	1300	900	1600	670	▲
400	15750	0	400	Dyn5	4.5	570	4100	52	1520	320	1210	850	1480	670	▲
400	10500	0	420	Dyn5	4	475	3480	0	1730	320	1140	820	1495	0	▲
500	22000	11000	420	Dyn11	4.4	710	5000	0	1750	320	1140	880	1600	0	▲
500	20000	0	400	Dyn5	4	730	5500	50	1660	365	1300	920	1860		▲
500	11000	0	420	Dyn11	4.5	710	4600	0	1690	320	1140	880	1450	0	▲
500	10000	0	690	Dyn5	4.6	500	4000	0	2200	350	1470	850	1560	0	▲
500	10000	0	400	Dyn11	4	1450	5800	53	1750	0	1450	970	1500	670	▲
630	35000	0	400	Dyn1	6	840	7000	52	2600	0	1450	900	1800	670	▲
630	22000	0	420	Dyn5	6	800	5600	60	2500	510	1400	1050	1700	670	▲
630	15750	0	400	Dyn5	4.5	720	6100	54	2035	400	1270	900	1600	670	▲
630	10000	0	400	Dyn5	6	800	8700	54	2040	445	1530	950	1690		▲
800	26000	0	400	Dyn11	6	1700	8500	68	2650	525	1700	950	2100	670	▲
800	21000	0	400	Dyn11	4.8	1030	6800	0	2300	380	1520	900	1700	0	▲
800	15000	10000	400	Dyn11	5	1940	8200	53	2200	0	1630	1080	1600	670	●
800	10000	0	400	Dyn5	6	1400	8500	56	2320	530	1400	1050	1890		▲
1000	35000	0	400	Dyn1	6	1600	9700	0	3100	0	1800	1050	1860	820	▲
1000	21000	0	400	Dyn5	6	1300	10200	56	2800	550	1970	980	1980	820	●
1000	15750	0	400	Dyn5	6	1300	10200	56	2790	550	1970	980	1980	820	●
1000	10000	0	400	Yyn0	5.3	1300	12200	0	2420	470	1670	1030	1590	0	▲
1250	26000	0	400	Dyn11	6	2360	13500	70	3550	760	2000	1100	2250	820	▲
1250	20000	15000	400	D(D)yn11	7.19	1320	16900	0	4140	1190	2345	1370	2310	820	●
1250	15000	10000	400	Dyn11	6	2600	13000	65	3600	0	1860	1250	1640	820	●
1250	10500	0	400	Dyn11	5.4	1460	13400	0	3000	580	1830	1150	1720	0	▲
1600	35000	0	400	Dyn1	6	2400	14000	0	4000	0	2000	1100	1900	820	▲
1600	20000	0	400	Yyn0	5.5	1780	16700	0	3320	680	1890	1170	1860	0	▲
1600	15750	0	400	Dyn5	6	1700	16000	58	3995	820	2100	1130	2250	820	●
1600	10000	0	690	Dyn5	5.7	1580	13500	0	3680	775	1910	1120	1970	0	▲
2000	30000	0	6300	Dyn5	6	3200	21000	71	5000	1100	2250	1300	2350	1070	●
2000	20000	0	400	Yyn0	6	2200	20100	0	4020	850	2010	1220	1910	0	▲
2000	15750	0	400	Dyn5	6	2100	19000	0	4710	900	2330	1360	2320	1070	●
2000	10000	0	6300	Dyn5	6	3200	21000	71	5000	1100	2250	1300	2350	1070	●

Please note that this table only shows a small sample of all product designs and ratings we supply.

▲ Hermetically sealed with corrugated tank ● Corrugated tank with conservator